

LEDI® 5

Indoor / Single face



Professional LED clock, robust and stylish combining the best of the technology for an easy installation and operation.



Time setting

The professional LEDI® clocks can display the same time information, synchronized by a master clock or a time server. Display date and time alternately

Key features

- Perfectly silent, direct and accurate reading of time.
- SMD LED technology.** Display in Red.
- The patented technology of the light guide provides a perfect regularity of the brightness and viewing angle at 160°.
- The front face of the LEDI® is coated with an antiglare and anti-scratch film giving an extraordinary 60000 : 1 level of contrast.
- A protection against over-voltage and industrial interference via EMC filter.
- An easy "plug and play" installation.
- An anodized aluminium case wall mount (screw lock) or flush mount.
- Its participation in the sustainable development, life span over 20 years.
- 2 years warranty.

Specification

Power supply	230VAC/50-60Hz 115VAC/50-60Hz Low voltage 24VDC
Certifications	CE, EN 60950, EN 55022, EN 55024, ROHS
Maximum consumption	6 VA
IP	30
MTBF	56 000 h.
MTTR	display : 5 min
Weight	~ 1kg
Dimensions	235x145 x62 mm (LxHxD)
Digit height	Hour/minute : 50 mm
Maximal distance of legibility	25 meters
Shock resistance	IK9
Operating temperature	-20° to 50°C
Electrical equipment classification	Classe 2 

Synchronization inputs

- AFNOR NFS 87500
- IRIG B : shall be specified on purchase order.



Display / LED specifications

Simple row LED display.
SMD Technology, Viewing Angle: 160°.

Red	245 mcd
-----	---------



LEDI® 5 Indoor / Single face

		ITEM CODE						
		N350						
		↑	↑	↑	↑	↑	↑	
VERSION								
AFNOR NFS 87500 / IRIG B receiver clock* <input checked="" type="checkbox"/>		8						
*IRIG.B Version : to be specified as « remark » on your Purchase Order.								
LED								
Red <input type="checkbox"/>		1						
MOUNTING								
Standard : wall mount** <input type="checkbox"/>			1					
Flush mount <input type="checkbox"/>			3					
** Please refer to the brackets technical sheet								
COLOUR OF CASE								
Standard : anodized aluminium <input type="checkbox"/>					7			
Black painted aluminium <input checked="" type="checkbox"/>					0			
Specific <input checked="" type="checkbox"/>					-			
POWER SUPPLY								
Standard : 230VAC/50-60Hz <input checked="" type="checkbox"/>						0		
115VAC/50-60Hz <input checked="" type="checkbox"/>						1		
Low voltage power supply: 24 VDC <input checked="" type="checkbox"/>						4		
OPTIONS								
Tropicalization <input checked="" type="checkbox"/>							U	