



# LEKO LED PROFILE



Strand Leko® LED Profile- the modern successor to the iconic Strand Leko that inspired generations of designers, this profile fixture is available in full color which uses a Red, Green, Blue, Amber, Lime & Cyan color mixing system for the mixable color spectrum. To compliment the Full Color version two white output versions, a warm tunable white (2700K to 4500K), and cold tunable white (4000K to 7000K) varieties, both of which offer a consistent CRI exceeding >94 CRI across all color temperatures.

The entire Leko family offer, far more than just in innovated color control, each of the fixtures utilizes new fan control technically and functions ensures these new high-powered LED fixtures are suitable for use in the quietest of applications.



To simplify installations, the Leko LED uses the SPX Smart Gate found on legacy SPX and PL4 fixtures and is compatible with existing SPX lenses, optional universal lens tube are also available for use with legacy Strand LEKO lens tube and other common lens systems.



# LEKO LED PROFILE

## FEATURES AND BENEFITS

- **High output midsized LED theatrical luminaires** - modern fixtures with quality you can trust
- **High CRI RGBALC Color System with SmartColor Control** - wide range of vivid color options that can be programmed using CYM
- **Tunable white with >94 CRI** - adjust color temperature without compromising output or quality of light
- **Independent color mixing and temperature controls** - match color palette to color temperature without manual adjustment for simpler programming
- **Quiet operation with variable fan control** - perfect for use in quiet environments
- **Adjustable frequency to exceed camera frame rates** - camera-friendly fixtures for IMAG, event recordings, or TV and film applications





# LEKO LED PROFILE

	FULL COLOR	TUNABLE WARM WHITE	TUNABLE COLOR WHITE
<b>SOURCE</b>			
<b>Type</b>	Luxeon C RGBAL LED	2700K+4500K	4000K+6500K
<b>Wattage</b>	91pcsx3W	91pcsx3W	91pcsx3W
<b>OPTICAL PERFORMANCE</b>			
<b>Dimming</b>	16-bit dimming; Dim snap on/off DMX control; Tungsten amber shift optional on/off DMX control	16-bit dimming; Dim snap on/off DMX control	16-bit dimming; Dim snap on/off DMX control
<b>Dimming curves</b>	Square Law Linear S-Curve	Square Law Linear S-Curve	Square Law Linear S-Curve
<b>CCT</b>	2,700 - 10,000k	2700 - 4500k	4000 - 6500k
<b>Strobe</b>	Standard, Lightning & Random	Standard, Lightning & Random	Standard, Lightning & Random
<b>Max output lumens all LED full</b>	8000	8500	9300
<b>CRI</b>	<b>RA</b>	>92 (CCT3200)	96
	<b>R9</b>	96.2	90
<b>TM30-15</b>	<b>Rf</b>	82	89
	<b>Rg</b>	116	98
<b>TLCI</b>	70	97	94
<b>Duv (Delta UV)</b>	0.00111	-0.00095	-0.00293
<b>TV flicker free</b>	Yes Adjustable 12 Hz-25 KHz	Yes Adjustable 12 Hz-25 KHz	Yes Adjustable 12 Hz-25 KHz
<b>BEAM</b>			
<b>Shutter</b>	4 blade shutter 360° continuous rotation	4 blade shutter 360° continuous rotation	4 blade shutter 360° continuous rotation
<b>Gobo</b>	B size gate / metal and glass	B size gate / metal and glass	B size gate / metal and glass
<b>COLOR CONTROL</b>			
<b>Color mixing</b>	RGBALC Direct control or CYM, CTO+ green magenta	<i>not applicable</i>	<i>not applicable</i>
<b>CTO / CTB</b>	Variable control 2,700 - 10,000K	Variable control 2,700 - 4,500K	Variable control 4,000 - 6,500K
<b>Camera adjustments</b>	Magenta / Green shift control	<i>not applicable</i>	<i>not applicable</i>



# LEKO LED PROFILE

	FULL COLOR	TUNABLE WARM WHITE	TUNABLE COLOR WHITE
<b>Color presets</b>	33 pre-defined calibrated colors; 20 user-definable color presets	<i>not applicable</i>	<i>not applicable</i>
<b>CONTROLS</b>			
<b>Control data protocols</b>	DMX RDM	DMX RDM	DMX RDM
<b>Data input</b>	5-pin DMX in/thru	5-pin DMX in/thru	5-pin DMX in/thru
<b>DMX modes</b>	Smart Color Control - 14 channels ( <i>default</i> ); Q Color Mode - 4 channels; Open Color Control - 19 channels	16 Bit - 7 channels ( <i>default</i> ); 8 Bit - 5 channels; 2 Ch - 2 channels	16-bit - 7 channels ( <i>default</i> ); 8 Bit - 5 channels; 2 Ch - 2 channels
<b>Fan control</b>	Fan On (Continuous) or Fan Auto	Fan On (Continuous) or Fan Auto	Fan On (Continuous) or Fan Auto
<b>Fan level preset</b>	Standard Studio Whisper	Standard Studio Whisper	Standard Studio Whisper
<b>User variable fan control</b>	User-definable variable fan speed level via DMX Whisper - Standard	User-definable variable fan speed level via DMX Whisper - Standard	User-definable variable fan speed level via DMX Whisper - Standard
<b>ACOUSTIC LEVELS @ 1M FULL OPERATION*</b>			
<b>Standard</b>	43	43	43
<b>Studio</b>	34	34	34
<b>Whisper</b>	30	30	30
* 30dBA base fan continuous mode			
<b>POWER</b>			
<b>Range</b>	100 - 240VAC	100 - 240VAC	100 - 240VAC
<b>Connector type</b>	Input/Thru	Input/Thru	Input/Thru
<b>Max wattage</b>	<b>120V</b>	<300W	<300W
	<b>240V</b>	<300W	<300W
<b>ENVIRONMENT</b>			
<b>Cooling system</b>	Forced air cooling	Forced air cooling	Forced air cooling
<b>Operating temp</b>	0-45°	0-45°	0-45°
<b>Construction</b>	Cast aluminum	Cast aluminum	Cast aluminum
<b>Standard finish</b>	Raven black	Raven black	Raven black
<b>IP rating</b>	IP20	IP20	IP20



# LEKO LED PROFILE

	FULL COLOR		TUNABLE WARM WHITE		TUNABLE COLOR WHITE	
<b>PHYSICALS</b>						
<b>Yoke</b>	Double clutch yoke with built-in short yoke adjustment		Double clutch yoke with built-in short yoke adjustment		Double clutch yoke with built-in short yoke adjustment	
<b>DIMENSIONS (H x W x D)</b>						
	<b>mm</b>	<b>in</b>	<b>mm</b>	<b>in</b>	<b>mm</b>	<b>in</b>
<b>Fixture only</b>	261 x 484 x 276	10.3 x 19 x11	261 x 484 x 276	10.3 x 19 x11	261 x 484 x 276	10.3 x 19 x11
<b>Packed</b>	380 x 355 x 623	15 x 14 x 25	300 x 355 x 623	380 x 355 x 623	300 x 355 x 623	380 x 355 x 623
<b>WEIGHT</b>						
	<b>kg</b>	<b>lb</b>	<b>kg</b>	<b>lb</b>	<b>kg</b>	<b>lb</b>
<b>Fixture only</b>	9.3	20.5	9.3	20.5	9.3	20.5
<b>Packed</b>	<b>Net</b>	TBC	TBC	TBC	TBC	TBC
	<b>Gross</b>	TBC	TBC	TBC	TBC	TBC
<b>SOFTWARE / FIRMWARE</b>						
<b>Update kit</b>	PEGASUS		PEGASUS		PEGASUS	
<b>WARRANTY &amp; APPROBATIONS</b>						
<b>Warranty</b>	2 Years		2 Years		2 Years	
<b>Approvals / listings</b>	CE, ETL, UL, FCC CSA, RoHS, ISO 9001		CE, ETL, UL, FCC CSA, RoHS, ISO 9001		CE, ETL, UL, FCC CSA, RoHS, ISO 9001	



# LEKO LED PROFILE

## FULL COLOR

LENS TUBE	LUX		FOOT CANDLES	
	5m	10m	16.4 ft	32.8 ft
5°	TBC	TBC	TBC	TBC
10°	TBC	TBC	TBC	TBC
14°	2640	767	245	71
19°	2300	549	214	51
26°	1200	302	111	28
36°	650	154	60	14
50°	500	105	46	10
70°	TBC	TBC	TBC	TBC
90°	TBC	TBC	TBC	TBC
<b>15-35°</b>				
Narrow	2308	577	214	54
Mid	1473	320	137	30
Wide	750	187	70	17
<b>25-50°</b>				
Narrow	1465	577	136	54
Mid	1117	280	104	26
Wide	672	167	62	16

## TUNABLE WARM WHITE

LENS TUBE	LUX		FOOT CANDLES	
	5m	10m	16.4 ft	32.8 ft
5°	TBC	TBC	TBC	TBC
10°	TBC	TBC	TBC	TBC
14°	3536	884	329	82
19°	3166	792	294	74
26°	1620	405	151	38
36°	870	217	81	20
50°	510	128	47	12
70°	TBC	TBC	TBC	TBC
90°	TBC	TBC	TBC	TBC
<b>15-35°</b>				
Narrow	3208	897	298	83
Mid	2485	612	231	57
Wide	1080	362	100	34
<b>25-50°</b>				
Narrow	2093	897	194	83
Mid	1768	617	164	57
Wide	1138	362	106	34



# LEKO LED PROFILE

## TUNABLE COLOR WHITE

LENS TUBE	LUX		FOOT CANDLES	
	5m	10m	16.4 ft	32.8 ft
5°	TBC	TBC	TBC	TBC
10°	TBC	TBC	TBC	TBC
14°	4046	1019	376	95
19°	3560	890	331	83
26°	2000	479	186	45
36°	980	246	91	23
50°	565	141	52	13
70°	TBC	TBC	TBC	TBC
90°	TBC	TBC	TBC	TBC
<b>15-35°</b>				
Narrow	3011	849	280	79
Mid	1675	457	156	42
Wide	1019	324	95	30
<b>25-50°</b>				
Narrow	4152	556	386	52
Mid	1947	447	181	42
Wide	876	229	81	21



# LEKO LED PROFILE

PRODUCT NAME	ORDER CODE
LEKO LED TCW, Tunable Cold White Light Engine and Gate c/w power input connector	<b>64505-001</b>
LEKO LED TWW, Tunable Warm White Light Engine and Gate c/w power input connector	<b>64505-002</b>
LEKO LED FC, Full color (RGBALC) Light Engine and Gate c/w power input connector	<b>64505-003</b>

LENS TUBES	ORDER CODE
5° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>TBC</b>
10° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>TBC</b>
14° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>SPX14LT</b>
19° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>SPX19LT</b>
26° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>SPX26LT</b>
36° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>SPX36LT</b>
50° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>SPX50LT</b>
70° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>TBC</b>
90° Fixed lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>TBC</b>
15-35° Variable zoom lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>SPX1535LT</b>
25-50° Variable lens tube, Compatible with LEKO LED, SPX, SPX LED and PL4 Light engines	<b>SPX2550LT</b>
Universal lens tube adaptor compatible with legacy LEKO lens tube and many third party lens tubes	<b>PL4UTA</b>

ACCESSORIES	ORDER CODE
Manual Iris (Fits Leko LED Gate)	<b>2180</b>
B sized Metal gobo holder (Fits Leko LED Gate)	<b>2160</b>
S sized glass gobo holder goes in iris slot (Fits Leko LED Gate)	<b>2178</b>

©2020 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Final detailed specifications to be published when the product is commercially released.

Ref: 64505-100-00