

StageLite SC

StageLite SC IP65



StageLite SC - # 10006A129
StageLite SC IP65 - # 10006A133

SPECIFICATIONS

- RGB+White color mixing
- Proportional zoom 11° - 34° (vertical beam, ½ peak angle)
- The light beam is generated by three independent optical planes (**Patent Pending**)
- Orientable beam from + 56° to - 52°, linear adjustment with manual positioning control: concentrate, symmetrical or asymmetrical
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- Flicker free, led frequency controlled by DMX
- Orientable standing feet
- Quick camlock clamps, on a modular guide with adjustable position
- Weatherproof rating IP 20 (StageLite SC), IP65 (StageLite SC IP65)

PHYSICAL SIZE

- Length: 308 mm (12.0 in)

- Width: 211 mm (8.3 in)
- Height: 181 mm (7.1 in)
- Weight: 6 kg (13.2 lbs)

LIGHT SOURCE

- 48 Seoul leds, 1.2 W each, 12 Red, 12 Green, 12 Blue and 12 White (6500 Kelvin)

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 8
- Setting and addressing: led display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug, with PowerCon connector (only IP 20 version)
- Power consumption: 0.5 A at 230 V, 1 A at 115 V
- DMX data in/out: 3 pin locking XLR

